

TOPAZE Opera

ELECTRIC CONVECTION OVEN

C04

TOPAZE Opera is a range of multi-purpose convection ovens. Their standard specification includes a steam injection system. They bake bread, viennoiserie, snacking and pastries alike perfectly.

The excellent air flow between the levels allows your products to develop fully and guarantees an even baking throughout the whole baking chamber.



specifications	
Number of levels	4
Spacing between levels	90 mm
Recommended baking trays	400 x 600 mm
Capacity (baked baguettes of 250g)	20
Weight	160 kg
Left hinged door	✓
Right hinged door	○
Easy-Touch control panel	✓
options and accessories	
Pastry Pack : speed variator and electrical damper	€
Grids 460 x 660	€
Stainless steel finishing	○
electricity	
Electrical supply	400V/TRI+N+T/50-60Hz
Power	10,5 kW
Rated current	16,3 A

legend

✓ standard ○ option € paying option


- + A control panel Easy-Touch on each deck that includes :
 - A *recipe book* with 50 programs.
 - An energy management thanks to the *Eco mode*.
 - An *Expert mode* to follow your energy consumption, the internal temperatures or the technical data of the oven.
- + The handle ensures a reliable locking and starts the timer as soon as the door closes.
- + The slide rails can be dismantled and make it possible to adjust the height of the trays for an easier access.
- + The interior glass door can be opened without any tools, allowing a deep cleaning and an easy access to the lighting located in the door.
- + The double glazing contributes to the good insulation of the oven and prevents from any risks of burning by reducing the surface temperature of the door.
- + **Fine Crust** system for the controlled drying of your pastries and delicate products.
- + The C04 can be adapted to 5 levels when baking pastries or other non voluminous products (75mm between the levels).

Accessories


- Hood with ventilator.
- Condenser with stainless steel casing.
- Stand H200 without slide rails, without feet, with wheels.
- Stand H760 with slide rails, feet and wheels.
- Stand H950 with slide rails, feet and wheels.
- False case H380, H570.
- Proofer with feet and wheels.

IMPLEMENTATION

DIMENSIONS AND CONNECTIONS




top view



Our selection

The configurations below respect an optimal height under hood of 1900mm, for an efficient and comfortable work.



#1

HOOD
FALSE CASE 380MM
TOPAZE C04B
STAND 950 MM
FEET

#2

HOOD
TOPAZE C04B
TOPAZE C04B
PROOFER

#3

HOOD
TOPAZE C04B
TOPAZE C04B
RETARDER PROOFER SF

#4


HOOD
TOPAZE C04B
TOPAZE C04B
STAND 760 MM
FEET

attention




Make sure to silicone the proofers and oven support when they when they are placed directly on the floor.

Connection on hood (responsibility of the client)



Connection to steam condenser (responsibility of the client)








side view

IMPLEMENTATION



WITH RETARDER PROOFER

Depending on your installation needs, the Topaze Opera configuration + retarder proofer is available in the following versions :


- with unit built into the Topaze hood;
- with unit integrated at the back of the retarder proofer.










Unit built in the hood






Integrated unit at the back



The elements below can be combined to form different Topaze ovens configurations :




tray capacity
C - 5 levels, 10 trays
L - 5 levels, 5 trays



TOPAZE = water inlet connection

SEBP:
Flexible pipe provided Lg 2,50m.
Female connection Ø20/27


Customer:
Water tap.
Male connection Ø20/27



TOPAZE = overflow outlet connection

SEBP:
Copper pipe
Ø10/12mm


Customer:
Flexible pipe needed between
the oven's outlet and the
waiting outlet on the floor.



TOPAZE = electrical connection



SEBP:
Electrical cable Lg 1,50m provided
L04/C04 : section 5 G 2,5 mm²
L10/C10 : section 5 G 6 mm²

Customer:
Plug connection male and
female ht 1,50m.



TOPAZE = steam connection

Customer:
Chimney Ø 125mm, stainless
steel wall simple isolated
needed. Connections according
local regulation.
(Ø100 without hood)



Non contractual drawings.